

Tire Supplies

Snap-In Valve Stems

These rubber snap-in style valves are made of quality EPDM rubber with brass threading and a pre-installed valve core. Max air pressure: 65 PSI



78015 TR413
1.25" length
0.453" hole



78016 TR415
1.25" length
0.625" hole



78017 TR412
0.88" length
0.453" hole



78018 TR413
1.25" length
0.453" hole



78019 TR414
1.50" length
0.453" hole



78020 TR418
2.00" length
0.453" hole



78021 TR600HP
• 1.25" length
• 0.453" hole
• Max air pressure:
80 PSI



78022 TR801XHP
• 1.25" length
• 0.625" hole
• Max air pressure:
100 PSI

Clamp-In Valve Stems

These straight brass clamp-in tubeless valve stems are for commercial applications. Fits all standard 5/8" valve stem holes and features EPDM grommet (rated up to 212° F).



78011 TR575
1-1/8" length




78006 TR501
1-1/2" length




78008 TR571
3-3/8" length



78005 TR500
2" length



78010 TR573
4-3/8" length



78007 TR570
3-1/8" length



78009 TR572
3-3/4" length

Valve Cores & Caps



78014
Nickel Plated



78044 Short High
Temperature (TRC-1)

AVT41 Wireless TPMS Tool

78003

This tool is quickly diagnoses issues with your vehicle's tire pressure monitoring system. Includes durable carrying case. Frequency Range: 315 MHz & 433 MHz.



TPMS Valve Stem Sensor



7800101 Silver Clamp-In
• OE Aluminum Ball-Seat
• Adjustable 12-40°



7800201 Rubber Snap-In
• EPDM Rubber
• Fixed Angle

TPMS Universal Service Kits

These kits contains all the components of the TPMS valve specific to each vehicle's make, model, and year.



78001 U1 TPMS Kit
• 97% market coverage of all metal valves & TPMS-Sensors

Each U1 kit includes:

- Universal nut
- Universal washer
- #1 & #2 grommets
- Valve core & cap



78002 U2 TPMS Kit
• 82% market coverage of all rubber valve stems

Each U2 kit includes:

- EPDM rubber snap-in valve
- Torx Screw

Heavy Duty Truck Valve Stems

These brass valve stems are nickel-plated and feature a 60° bend. Long-lasting Viton Rubber o-ring resists oxidation and other elements better than natural rubber. Fits 9.7mm diameter aluminum rim holes. Max air pressure: 200 PSI.



78012 TR544D
1.94" length

78013 TR545D
2-1/2" length

Tire Repair Patches



78029 Small
1-11/16" (40 patches)



78030 Medium
2-1/4" (30 patches)



78031 Large
3-1/8" (20 patches)



78032 Standard
2-5/8" (25 patches)



78033 Small
1-5/8" (100 patches)



78034 Medium
2-1/4" (50 patches)



78035 Large
3-1/4" (25 patches)



78042 TPMS with Seal



78041 Generic

78004 V2B Double Seal Gator Cap




78043 Long Skirted TPMS with Seal




Tire Supplies



Wheel Weights





- P-Series Lead**
- 78060 0.50 oz
 - 78061 0.75 oz
 - 78062 1.00 oz
 - 78063 1.25 oz
 - 78064 1.50 oz
 - 78065 1.75 oz
 - 78066 2.00 oz



- P-Series Zinc**
- 78070 0.50 oz
 - 78071 0.75 oz
 - 78072 1.00 oz
 - 78073 1.25 oz
 - 78074 1.50 oz
 - 78075 1.75 oz
 - 78076 2.00 oz





- MC-Series Lead Uncoated**
- 78080 0.50 oz
 - 78081 0.75 oz
 - 78082 1.00 oz
 - 78083 1.25 oz
 - 78084 1.50 oz
 - 78085 1.75 oz
 - 78086 2.00 oz




- MC-Series Lead Coated**
- 78090 0.50 oz
 - 78091 0.75 oz
 - 78092 1.00 oz
 - 78093 1.25 oz
 - 78094 1.50 oz
 - 78095 1.75 oz
 - 78096 2.00 oz




- MC-Series Zinc Coated**
- 78100 0.50 oz
 - 78101 0.75 oz
 - 78102 1.00 oz
 - 78103 1.25 oz
 - 78104 1.50 oz
 - 78105 1.75 oz
 - 78106 2.00 oz



- FN-Series Lead Coated**
- 78110 5g
 - 78111 10g
 - 78112 15g
 - 78113 20g
 - 78114 25g
 - 78115 30g
 - 78116 35g




- FN-Series Zinc Coated**
- 78120 5g
 - 78121 10g
 - 78122 15g
 - 78123 20g
 - 78124 25g
 - 78125 30g
 - 78126 35g




- 78131** Roll Steel 0.25 oz (704 segments)




- 78130** Steel 0.25 oz (576 segments)




- 78132** Black Steel 0.25 oz (576 segments)




- 78136** Low-Profile Steel 0.50 oz (224 segments)



- 78137** Black Steel 0.50 oz (224 segments)



- 78138** Steel 0.50 oz (352 segments)



Quikstik® Adhesive Wheel Weights




- 78127** Lead 0.25 oz (624 segments)




- 78128** Steel 0.25 oz (624 segments)



- 78133** Lead 0.50 oz (360 segments)



- 78134** Steel 0.50 oz (360 segments)




- 78129** Roll Steel 0.25 oz (1280 segments)
- 78135** Roll Steel 0.50 oz (640 segments)



Lead Wire Combination Unit



- 78036** 5/16" Stem
- 78037** 3/8" Stem



Tire Repair



- 78028** (Gallon) Tire Mounting Lubricant



- 78027** (32oz) Bead and Rim Sealer



- 78026** (8oz) Universal Cement



- 78023** (6.5lb) Tire Paste Mounting Compound



- 78025** (16oz) Inner Liner Sealer



- 78024** (1qt) Liquid Buffing Solution

Universal String Type Inserts



- 78038**
- 78039**



- 78040**

